



"TL" Series Features Four-Way Mount

Mount in Conventional or Reverse Direction with the header tee pivot up or inverted for advantages such as weight transfer to front axle, low mounting and ease of installation.



C90



BODY PROP



H.D. REAR HINGE



DH90



TL2627

UNDERBODY OPTIONS



GEAR PUMP, VALVE, RESERVOIR COMBO



STANDARD REAR HINGE



NTC 8000XT



12 VOLT DC POWER PACK



HYDRAULIC CYLINDER

MODEL	C90	DH90	TL1522	TL1627	TL2522	TL2627	NTC 8000XT
No. of Cylinders	1	1	1	1	2	2	2
Cylinder Bore (Inches)	5	5	5	6	5	6	4
Piston Stroke (Inches)	14	16	20	27	20	27	91
Piston Rod Dia. (Inches)	2.25	2.25	2.25	2.5	2.25	2.5	TELESCOPIC
Mounting Height (Inches)							
Low-Mount Installation	N/A	6.5	7.75	7.75	7.75	8.75	9.5
Hi-Mount Installation	10.75	6.5	12.75	12.75	12.75	12.75	9.5
Recommended Long Beams (Ins)							
Low-Mount Installation (With or Without 4" Cross Sills)	N/A	6	7	7	7	8	8
Hi-Mount Installation (Without Cross Sills)	10	6	12	12	12	12	9
Weight – Approx. (Pounds)	336	444	598	800	887	1187	880

DEMAND  NORDIC POWER
FOR RUGGED DEPENDABLE LIFT PERFORMANCE